

342-505 HD Tire Swivel

Rev 03.24/03

- *Heavy-Duty With Rubber Boot Which Shields the Universal Joint
- *Complete with Grease Fittings for Easy Maintenance
- *Three-Point Mounting System Reduces Tangles and Pinching

Includes the following hardware:

- 4-116-618 3/8" x 4 1/2" Hex Bolts
- 8-316-601 3/8" Flat Washers
- 4-226-601 3/8" Lock Nuts
- 2-196-613 3/8" U-Bolts for 3 1/2" O.D. Top Rail



Hardware is supplied for mounting on wood top rails (use flat plate) or 3 1/2" O.D. pipe top rails (use U-bolts)

Multi Axis Swings:

The Use/Fall Zone should extend in all directions the length of the swing plus six feet. The six-foot minimum fall zone from the supporting structure also applies, and may overlap the six-foot zone of an adjacent swing structure.

General Maintenance Instructions:

Check MONTHLY for loose bolts, damaged or broken parts. Tighten and/or replace immediately. On swings and any equipment that uses S-hooks and/or swing hangers check the bearing surfaces for wear. Replace any parts that show a reduction of 25% from the original size. Check swivel assembly to make sure it is full of grease, if not fill with grease to prevent excessive wear on bearing.

1 CTN. 1 total piece Wt. 10 lbs., Class 70